


## 120mm CONCRETE + 300mm PODS




TIMBER FRAMED WALL WITH BOTTOM PLATE FIXING TO MAXRAFT SPECIFICATION. SLAB AND REINFORCING AS PER ENGINEERS DRAWINGS MAXRAFT PLUS 420 MAXEDGE T40 1200 X1200 X 300mm DPM (TYPICAL).--<sup>/</sup> 50 **|**-300 SOLID POD. COMPACTED HARDFILL





GARAGE DOOR REBATE DETAIL

**EXTERNAL FOOTING DETAIL** MAXEDGE T105 - 90mm FRAMING



**EXTERNAL FOOTING DETAIL** 


MAXEDGE T40 - 140mm FRAMING

**BRICK / STONE VENEER** REBATE DETAIL

SLAB AND REINFORCING AS PER ENGINEERS DRAWINGS

1200 X1200 X 300mm

SOLID POD.



1200 X1200 X 300mm 300 min

INTERNAL FOOTING DETAIL

SLAB AND REINFORCING AS PER ENGINEERS DRAWINGS

INTERNAL RIB DETAIL

DETAILS).

FALL SLAB LOCALLY (50mm MAX.) OR CREATE 50mm RECESS FOR TILED SHOWER (REFER TO ARCHITECTS DRAWINGS FOR

1200 X1200 X 250mm

**THERMAL BREAK** 


300

350


50

300

FREE JOINT / CONTROL JOINT DETAIL



350



1200 X1200 X 250mm

SOLID POD.

FALL SLAB LOCALLY (50mm MAX.)
OR CREATE 50mm RECESS FOR
TILED SHOWER (REFER TO
ARCHITECTS DRAWINGS FOR
DETAILS).

SHOWER RECESS DETAIL - 90mm FRAMING.

SHOWER RECESS DETAIL. SHOWER RECESS DETAIL - 140mm FRAMING.

MAXRAFT PLUS 420

DATE: 28/11/2023